

WATERFRONT FACILITY COMPLIANCE BOOKLET

NAME:		
FIN:	MOBILE UNIT #	
СОТР:		
DATE:		
CC TEAM LEADED.		

DEPARTMENT OF TRANSPORTATION, U.S. COAST GUARD, CG-5562A (Rev 6-04)

INSTRUCTIONS

- Initial the approriate block if it applies. Line out and N/A the non-applicable sections. 2.
- Complete the pre-inspection check list prior to commencing the examination. Record all discrepancies opposite the item. 3.

- Complete a diary entry for your exam.
 Sign the back of the booklet in the appropriate section.
- 7.
- Insure that the facility representative receives an initial copy of the inspection report. Complete COTP's review and transmit Letter of Inspection signed by COTP.

PRE-INPSECTION CHECK LIST

]]	1.	Conduct a complete review of the facility's file.
]]	2.	Determine type of facility and the applicability of the regulations. [] Designated Waterfront Facility Section 1 [] LNG Facility Section 2 [] LHG Facility Section 3 [] Bulk Liquid Facility Section 4 [] Mobile Bulk Liquid Facility Section 5 [] MARPOL Reception Facility Section 6 [] Passenger Terminal Section 7
]]	3.	Print out the appropriate checklist sections. Cover page, Instructions Page, and Sections 8 and 10 should always be printed.
[]	4.	Conduct a complete review of the facility's Operations Manual.
[]	5.	Determine if the facility has any approved "Alternatives." Note in remarks.
[]	6.	Determine if the facility has any approved "Exemptions." Note in remarks.
[]	7.	Does the facility have a Letter of Intent?
[]	8.	Conduct a review of the facility's Security Plan as applicable.
[]	9.	Does the facility have a Letter of Approval?
[]	10.	Is the Operations Manual and Emergency Manual marked "Examined by the Coast Guard?" (if required)
[]	11.	Does the facility have a current Pollution Response Plan? (33 CFR 154.1025)
]]	12.	Does the facility use a vapor control system? (33 CFR 154.800) [] A. Has it been certified? [] B. Is a copy of the certificate on file?
[]	13.	Note the last date of previous inspection/survey
[]	14.	Note the last date of any required test or inspections.
[]	15.	Print out the MSLE facility file for this facility and verify the information during the inspection.
[]	16.	Has a Physical Security/Vulnerability Assessment been conducted and is it on file? (MSM Vol. 7, Chap. 2.c.1) [] Yes. Consider new assessment if significant changes at facility. [] No. Conduct initial assessment.

^{**}Inspectors are cautioned to wear all required personal protection equipment. The facility file should be reviewed to identify all potential cargo and equipment hazards that could be encountered during the inspection. Inspectors will comply with all of the facility's personal protection requirements in addition to Coast Guard requirements.**

SECTION 1.

DESIGNATED WATERFRONT FACILITY INSPECTION (33 CFR 126)

A. CONDITIONS FOR DESIGNATION

1.	[]	Fire Extinguishing Equipment 126.15(a)(1) Available and maintained in adequate quantities, locations, and types.	Remarks
			Must meet State and Local laws or NFPA 10, 13, 14, & 307	
2.	[]	Marking of Fire Appliance Locations 126.15(a)(2) location of all fire appliances, including hydrants, standpipe and hose stations, fire extinguishers and fire alarm boxes are conspicuously marked and readily accessible according to NFPA . 10, 13, 14, and 307	
3.	[]	Warning Signs 126.15(a)(3) Constructed and installed in accordance with NFPA 307, CH 7-8.7	
4.]]	Lighting 126.15(a)(4) If the facility transfers dangerous cargo between sunset and sunrise: Must have outdoor lighting that adequately illuminates the transfer work area	
			Must be installed and maintained in accordance with NFPA 70	
5.	[]	International Shore Connection 126.15(a)(5) If the facility receives foreign flagged vessels, the facility must have an International Shore Connection in meeting ASTM F-1121	
6.	[]	Access to the Facility 126.15(a)(6) Whenever dangerous cargo is transferred or stored on the facility access to the facility must be limited	
7.]]	Security Measures 126.15(a)(7) Guards must be stationed, or equivalent controls, to deter and detect: Unlawful entrance Detect and report fire hazards and fires Detect and report releases of dangerous cargos and hazardous materials Check the readiness of protective equipment Report emergency situations at the facility.	
8.	[]	Material Handling Equipment 126.15(a)(9) When dangerous cargo is being transferred or stored on the facility, material handling equipment, trucks, and other motor vehicles operated by internal combustion engines must meet NFPA 307 CH 9	
9.	[]	Smoking 126.15(a)(10) Allowed on the facility where permitted by State and Local Law	
			"No Smoking" signs must be conspicuously elsewhere on the facility	
10.	[]	Rubbish and Waste Material 126.15(a)(11) Must be placed in adequate waste receptacles	

Fa	cil	itie	s that handle dangerous cargo not in transportation units	126.15(b)
11.	[1	Arrangement of Cargo 126.15(b)(1) Cargo, freight, merchandise, or material on the facility must be arranged to provide access for firefighting and clearance for fire prevention according to NFPA 307, CH 8-5	
12.	[]	Portable Fire Extinguishers 126.15(b)(2) Adequate quantities and locations	
			Meets requirements of NFPA 10	
			Inspected and maintained in accordance with NFPA 10	
13.	[1	Electrical Systems 126.15(b)(3) All new electrical equipment and wiring must be of the same type And installed as specified under NFPA 70	
			Defective and dangerous electrical equipment and wiring must be Promptly repaired, replaced, or permanently disconnected	
14.	[1	Heating Equipment 126.15(b)(4) Open fires and open-flame lamps are prohibited	
			Heating equipment must meet NFPA 307 Ch 9-4	
15.	[1	Maintenance Stores and Supplies 126.15(b)(5) Hazardous materials may be stored only in amounts necessary for Normal operating conditions.	
			Must be stored in compartments that are: Remote from combustible Materials Constructed to provide safe storage Kept clean and free of scrap materials, empty containers, soiled wiping rags, waste, and other debris	
Fa	cil	itie	s that handle dangerous cargo in transportation units 1	26.15(c)
16.	[]	Terminal Yards 126.15(c)(1) Must conform to NFPA 307 Ch 5	
16.	[1	Containers 126.15(c)(2) Containers packed with dangerous goods can not be stacked more	
			than four high	

В.	<u>C</u>		IDITIONS FOR FACILITY OF PARTICULAR IAZARD	
1.	[]	Conditions for Facility of Particular Hazard 126.16 Warning alarms installed (siren or rotating flashing light).	
			Heard or seen for 1 mile during normal facility working conditions.	
C.	<u>S</u>	ΤO	WAGE AND HANDLING OF DANGEROUS CARGOES	
1.	[]	Permits Required for Handling Designated Dangerous Cargo 126.17	
			Handling, loading, discharging, or transporting designated dangerous cargo without a permit issued by the COTP.	
			Permit waived under conditions of 33 CFR 126.17?	
2.	[]	Quantity of Designated Dangerous Cargo 126.19 Not exceeding limits specified by permit.	
3.	[]	Permitted Transactions 126.21	
			No excess dangerous cargo present	
			Dangerous cargo present incident of its prompt transhipment	
4.	L]	General Permit for Handling Dangerous Cargoes 126.27	
			Prior notification of COTP.	
			No prohibited Class I (explosive) or other dangerous cargos	
			Break-bulk dangerous cargo must be segregated according to 49 CFR 176.83(a) through (c)	
			Transport units and portable tanks containing dangerous cargo must be segregated according to 49 CFR 176.83(a), (b), and (f)	
			Break-bulk dangerous cargo must be segregated from transportation Units containing dangerous cargo according to 49 CFR176.83(e)	
			Solid dangerous cargo must be separated to prevent interaction of	
			incompatible materials in the event of an accident 49 CFR 176.83	
			Division 4.3, 5.1 and Class 8 must be stored in a manner that prevents them from contacting water	
			Class 8 and Division 5.1 must be handled and stored so that in the event of a leak they do not come in contact with organic material	
			Dangerous cargo stored on the facility must be arraigned in a manner that retards the spread of fire	
			Dangerous cargo stored on the facility must be packaged, marked and labeled in according to 49 CFR parts 171 – 180	
			Class 7 material must be stored as specified in 49 CFR 173.447	
			2	

5. []	Ammonium Nitrate, Ammonium Nitrate Fertilizers, fertilizer Mixtures, or Nitro Carbo	
	Nitrate; General Provisions 126.28	
	- outside containers marked with proper shipping name.	
	- storage building constructed to afford good ventilation.	
	 storage at safe distance from electric wiring, steam pipes, radiators, or any heating mechanism. 	
	- separated by fire resistant wall or 30 ft from organic materials or	
	other chemicals and substances which could cause contamination.	
	 storage in clean area, upon clean wood dunnage or pallets over clean floor. 	
	- may be directly on floor if concrete floor, covered with moisture barrier.	
	- abundant fire fighting water available	
	- drains, traps, pits or pockets eliminated or plugged.	

SECTION 2.

LNG FACILITY INSPECTION (33 CFR 127 Subpart B)

Α.	<u>GE</u>	:Nt	<u>ERAL</u>	Remarks
1.	[]	Letter of Intent 127.007	
			 properly submitted for new facility, at least 60 days before construction begins; inactive existing facility, at least 60 days before transfer; contains all information required in 33 CFR 127.007(d). 	
			- written notice of changes.	
			 written notice if no LHG/LNG transfer operations scheduled within next 12 months. 	
2.	[]	Inspections of Waterfront Facilities 127.011	
			- operator allowing examination	
3.	[]	Alternatives 127.017	
			- conduct a file review for COTP approved alternatives to the regulations. Ensure compliance. Facility copy readily available.	
4.	[]	Operations Manual and Emergency Manual 127.019	
			- manuals marked "Examined by the U.S. Coast Guard."	
В.	W/		ERFRONT FACILITIES HANDLING LIQUIFIED ATURAL GAS	
1.	[]	Design and Construction: General 127.101	
			- meets criteria in NFPA 59A.	
2.	[]	Piers and Wharves 127.103	
			- designed to resist earthquakes, if necessary.	
			- substructures: - made of concrete or steel;	
			- fire endurance rating > 2 hrs.	
			 storage tanks volume necessary for: surge protection; pump suction supply; 	-
			- other process needs	

3.	[]	Layout and Spacing of Marine Transfer Area for LNG 127.105	Remarks
			- impounding spaces	
			- loading flange located at least 300 meters from:	
			- each bridge crossing navigable waterway;	
			- each entrance to any tunnel under navigable waterway.	
4.	[]	Electrical Power Systems 127.107	
			- separate emergency power source.	
			- meets National Electrical Code, NFPA 70.	
			- emergency power source provides enough power for:	
			- emergency shutdown system;	
			 communications equipment; firefighting equipment; 	
			- emergency lighting.	
			- auxiliary generator meets Section700-12 of NFPA 70.	
_	_			
5.	L	1	Lighting Systems 127.109	
			- separate emergency lighting.	
			- not confused with any ATON or interfere with navigation.	
			 provide average illumination 1 meter above deck that is: loading flange = 54 lux; 	
			- work area = 11 lux.	
			- emergency lighting provides lighting for:	
			- emergency shutdown system;	
			communications equipment;firefighting equipment.	
6.	Г	1	Communications Systems 127.111	
	•	•		
			- ship to shore communications.	
			- separate emergency system.	
			- dedicated to allow voice communication between PICs and	
			personnel in control room.	
7.	[]	Warning Signs 127.113	
			- seen from shore and water.	
			- have the following text:	
			Warning	
			Dangerous Cargo No Visitors	
			No Smoking	
			No Open Lights	
			- letters are block style, black on white, and 3 inches high.	

8.	[1	Sensing and Alarm Systems 127.201	Remaks
	-	-	- fixed sensors:	
			- audio and visual alarms in control room;	
			- audio alarms nearby.	
			- fixed sensors continuously monitoring vapors:	
			in each enclosed area;meet Section 9-4 of NFPA 59A.	
			fixed concern continuously manifesting for flows, boot, or products	
			 fixed sensors continuously monitoring for flame, heat, or products of combustion: 	
			 in each enclosed or covered Class I, Division 1, hazardous location defined in Section 500-5(a) of NFPA 70; 	
			- in each area in which flammable or combustible material is	
			stored; - meet Section 9-4 of NFPA 59A.	
9.	г	1	Portable Gas Detectors 127.203	
Э.	L	1		
			- at least 2 in transfer area.	
			- capable of measuring 0-100% of lower flammable limit of methane.	
10.	[]	Emergency Shutdown 127.205	
			- can be activated manually.	
			 activiated automatically when fixed sensors measure concentrations exceeding 40% of lower flammable limit. 	
11.	г	1	Warning Alarms 127.207	
• • • •	L	1	Walling Alarms 127.207	
			- rotating or flashing amber light.	
			- siren.	
			- light and siren unobstructed for 1 mile in all directions.	
12.	г	,	Persons in Charge of Shoreside Transfer	
12.	L	1	Operations: Qualifications and Certification	
			127.301	
			- at least 48 hrs LNG transfer experience.	
			- knows hazards of LNG.	
			- knows rules in 33 CFR 127.	
			- knows procedures in Ops and Emergency Manuals.	
			- certification in writing available for inspection at facility.	

13. []	Operations Manual 127.305	Remarks
	 contains description of transfer system: mooring areas; 	
	- transfer connections;	
	- control rooms;	
	- diagrams of piping and electrical systems.	
	- duties of transfer personnel.	
	- maximum relief valve setting.	
	- maximum allowable working pressure.	
	- facility telephone numbers for:	
	- supervisors; - PICs;	
	- personnel on watch;	
	- security personnel.	
	- description of security system.	
	- description of security system.	
	- procedures for:	
	- transfer operations;	
	 transfer operation start-up and shutdown; security violations; 	
	- communications systems.	
	- description of training program.	
14. []	Emergency Manual 127.307	
	- LNG release response procedures.	
	- emergency shutdown procedures.	
	- description and operating procedures for fire equipment/systems.	
	- description of emergency lighting and power systems.	
	telephone numbers for:local USCG units;	
	- hospitals;	
	- fire departments;	
	 police departments; other emergency reponse organizations. 	
	- other emergency reponse organizations.	
	- location and provisions of personnel shelters.	
	- first aid procedures, location of first aid stations.	
	- emergency procedures for mooring/unmooring a vessel.	

15. [1	Motor Vehicles 127.311	Remarks
		designated parking spaces:do not block fire lanes;do not impede any exits;	
		not located in impounding space;not within 15 meters of any storage tank or loading flange.	
		 no parking in non-designated space or refueling during transfer operations. 	
16. [1	Bulk Storage 127.313	
	•	Bank Storago 1271010	
		 flammable liquids stored in transfer area: only those allowed by 127.313(a) stored IAW Chapter 4 of NFPA 30. 	
17. []	Declaration of Inspection 127.317	
		- available for all transfers within last 30 days.	
		 properly completed with the following information: name of vessel and facility: 	
		- date and time transfer operations started;	
		 list of requirements per 127.315 with initials of facility PIC after each requirement; 	
		 signature of facility PIC, date and time of signing; signature of each relief PIC, date and time of each relief. 	
18. []	Records 127.409	
		- description of the components tested under 127.407.	
		- date and results of tests under 127.407.	
		- desription of any corrective action taken after tests.	
		- available for all tests within the last 24 months.	
19. []	Training: General 127.503	
		full time employees:basic LNG firefighting procedures;	
		- LNG properties and hazards.	
		 additional training for persons assigned for transfer operations: examined Operations and Emergency Manuals; 	
		- advanced LNG firefighting procedures;- security violations;	
		 LNG vessel design and cargo transfer operations; LNG release response procedures; 	
		- first aid for frostbite, burns, CPR, transporting injured personnel.	

- refresher training at least once every 5 yrs.

20. []	Fire Equipment: General 127.601	Remarks
	rad or come other congrisuous colors	
	 red or some other conspicuous color: hydrants and standpipes; 	
	- hose stations;	
	portable fire extinguishers;fire monitors.	
	- fire monitors.	
	- if applicable, bears approval of one of the following:	
	- Underwriters Laboratories, Inc.;- Factory Mutual Corp.;	
	- Coast Guard.	
04 - 1	B (
21. []	Portable Fire Extinguishers 127.603	
	- meet 9-6.1 of NFPA 59A and Chapter 3 of NFPA 10.	
	- at least one in each designated parking area.	
22. []	Emergency Outfits 127.605	
	- one suit for each person whose duties include fighting fires, but at	
	least 2.	
	- must include the following:	
	 explosion proof flashlight; boots and gloves of rubber/electrically nonconducting material 	
	- rigid helmet;	
	- water/fire resistant clothing;	
	- U.S. Bureau of Mines approved SCBA.	
	- readily accessible and marked for easy recognition.	
	5' W ' O ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	
23. []	Fire Main System 127.607	
	- provides at least 2 water streams to each LNG transfer piping and	
	each connection, one of which from a single length of hose or fire	
	monitor.	
	- isolations valves:	
	- at least one at each branch connection;	
	- at least one downstream of each branch connection.	
	- capacity:	
	 simultaneously supply all hydrants, standpipes, and fire monitors; 	
	- supply the two outlets with greatest pressure drop between	
	source of water and the hose or monitor at a pitot tube pressure	
	of 75 psi.	
	- at least one pressure relief valve, if capable of supplying at greater	
	than design working pressure.	
	- fire hose:	
	- at each hydrant or standpipe;	
	- at least 1 1/2 in diameter and 100 ft or less in length;	
	 - on hose rack or reel; - connected to hydrant or standpipe; 	
	- has USCG approved nozzle.	

24. []	Dry Chemical Systems 127.609	Remarks
	- provides at least 2 discharges to area surrounding	oading arm.
	and must be	
	one must be:from a monitor;	
	 actuated and, except for pre-aimed montiors, co location other than the monitor. 	ntrolled from
	- capacity to supply simultaneously or sequentially e	ach hose or
	monitor for 45 seconds.	
	- at least one length of hose at each hose station:	
	- on hose rack or reel;	si.
	- nozzle with a valve that stops flow of dry chemic	
25. []	International Shore Connection 127.	
	- IAW ASTM F-1121.	
	- 2 1/2 in. fire hydrant.	
	- 2 1/2 in. hose of sufficient length to connect hydrar	t to vessel.
26. []		
20. []	HOLWOIK 127.017	
	- permit from COTP?	
27. []	Security on Existing Facilities 127.70	1
	- past security procedures and arrangements continu	
	maintained or upgraded whenever LNG transfer or conducted.	perations are
00 []		
28. []	Access to the Marine Transfer Area for 127.703	LNG
	- access limited to:	
	personnel who work at facility;USCG personnel;	
	- other personnel authorized by operator.	
	- personnel must have:	
	facility issued ID or other ID with photo;visitor's badge and escort.	
29. []	Security Systems 127.705	
	- security patrols once every hour, or	
	- manned television monitoring system used to detec	t:
	- unauthorized personnel;	
	- fires; - LNG releases.	
20 [1	Sacurity Davagna	
30. []	Security Personnel	
	- instructed on security violation procedures.	

31. []	Protective Enclosures 127.709	Remarks
	- fence or wall that prevents trespassing.	
	- around:- impounding spaces;- control rooms and stations;- electrical power sources.	
32. []	Communications 127.711	
	 direct communications between security patrol and other operating or security personnel on duty on the facility. 	

SECTION 3.

LHG FACILITY INSPECTION (33 CFR 127 Subpart C)

Α.	GE	N	<u>ERAL</u>	Remarks
1.	[]	Letter of Intent 127.007	
			 properly submitted for new facility, at least 60 days before construction begins; inactive existing facility, at least 60 days before transfer; contains all information required in 33 CFR 127.007(d). 	
			- written notice of changes.	
			- written notice if no LHG/LNG transfer operations scheduled within next 12 months.	
2.	[]	Inspections of Waterfront Facilities 127.011	
			- operator allowing examination	
3.	[]	Alternatives 127.017	
			- conduct a file review for COTP approved alternatives to the regulations. Ensure compliance. Facility copy readily available.	
4.	[]	Operations Manual and Emergency Manual 127.019	
			- manuals marked "Examined by the U.S. Coast Guard."	
В. 1	w	ΔTI	ERFRONT FACILITIES HANDLING LIQUIFIED	
•			AZARDOUS GAS	
1.	[]	Piping Systems 127.1101	
			- designed and constructed IAW ASME B31.3.	
			 not exposed to physical damage from vehicular traffic or cargo- handling equipment. 	
			- if under navigable waters: meets 49 CFR 195.248.	
			 isolation valve with bleed connection: at transfer manifold of each transfer line and vapor return line; transfer hoses/loading arms can be blocked off, drained or 	
			pumped out, and depressurized before disconnecting; - bleeds or vents to safe area.	
			- isolation valve located at edge of marine transfer area: - each tansfer line and vapor return line; - readily accessible.	

			- power-operated isolation valve:	Remarks
			 timed to not produce hydraulic shock; layout of piping allows valve to close in 30 seconds without 	
			creating excessive stresses.	
			- vapor return line designed to attach to vessel's vapor connection.	
			 manifolds marked to indicate LHGs handled (for facilities handling 2 or more LHGs). 	
			- precautions against static, lightning, and stray currents IAW API RP 2003.	
2.	[]	Transfer Hoses and Loading Arms 127.1102	
			- transfer hose:	
			 made of material resistant to LHGs transferred; withstand temperature/pressure during transfer; 	
			- MAWP not less than maximum pressure which may be	
			subjected and at least 1030 kPa guage (149.4 psig); - minimum bursting pressure at least 5x MAWP;	
			- have:	
			= full threaded connections;= flanges meeting ANSI B16.5, or	
			= quick connect couplings acceptable to COMDT;	
			 adequately supported against weight; no kinks, bulges, soft spots or other defects; 	
			- permanently atteched nameplate or other mark indicating:	
			each LHG for which it is suitable;MAWP and service temperature;	
			= minimum service temperature.	
			 loading arms: made of materials resistant to LHGs transferred; 	
			- withstand temperatures/pressure during transfer;	
			- adequately supported against weight;	
			 alarm or person indicating approach of extension limit; permanently attached nameplate or other mark indicating: 	
			each LHG it may handle;MAWP and service temperature;	
			= minimum service temperature.	
3.	[]	Piers and Wharves 127.1103	
			- comply with standards in 49 CFR part 41.	
			- fire endurance rating not less than 2 hrs:	
			- substructures on new facility;	
			- new consturction in LHG transfer area of existing facility.	
4.	[]	Layout and Spacing of Marine Transfer Area for LHG 127.1105	
			- accumulation of flammable/toxic gases prevented within structures.	
			- impounding space designed/located so that heat flux from fire over	
			space does not cause damage to a vessel, preventing	

movement.

			- manifolds, loading arms, independent mating flanges:	Remarks
			- at least 60 meters (197 ft) from bridge crossing navigable	
			waterway or tunnel entrance/superstructure under a navigible waterway, if used by general public or railway;	
			- at least 30 meters (98.5 ft) from public roadway or railway.	
5.	[]	Electrical Systems 127.1107	
			- specified by and IAW NFPA 70.	
•		,		
6.	L	J	Lighting Systems 127.1109	
			- transfers of LHG between sunrise and sunset?	
			[] yes	
			- if yes, outdoor lighting illuminates marine transfer area.	
			- located or shielded so that it is not:	
			- mistaken for ATON;	
			- interferring with navigation.	
			- minimum average illumination on horizontal plane 1 meter above walking surface:	
			- 54 lux (5 foot-candles) at any loading flange;	
			- 11 lux (1 foot-candle) for remainder of transfer area.	
7.	[]	Communications Systems 127.1111	
			- 2-way voice between PICs on vessel and facility.	
			- usable in all phases of transfer and all weather.	
			 devices listed as intrinsically safe by NFPA recogninzed independent laboratory. 	
0	r	,	Warning Signs 127 1112	
8.	L	1	Warning Signs 127.1113	
			- can be seen from shore and water	
			- bear the following:	
			Warning	
			Dangerous Cargo	
			No Visitors	
			No Smoking No Open Lights	
			No Open Lights	
			Note: "No smoking" and "No Open lights" may be omitted when	
			LHG being transferred is not flammable.	
			- each letter on sign must be:	
			- block style;	
			- black on white background;	
			- at least 7.6 cm (3 inches) high.	

9. []	Gas Detection 127.1203	Remarks
	 flammable gas detectors: at least 2 portable or 1 fixed in marine transfer area; 	
	- indicates whether concentration exceeds 30% of Lower Flammable Limit for each flammable product;	
	- meets ANSI S12.13, Part 1.	
	toxic gas detectors:at least 2 portable or 1 fixed in marine transfer area;	
	- indicates whether concentration is above, at or below any Permissible Exposure Limit listed in 29 CFR 1910.1000, Table	
	Z-1 or Z-2.	
	each gas detector sevres to:detect leaks;	-
	check structures for gas accumulation;indicate worker's exposure to toxic gases.	
10. []	Emergency Shutdown 127.1205	
	- each piping system has a quick-closing shutoff valve.	
	 located as close as practicable to terminal manifold or loading- arm connection; 	
	close on loss of power;close in 30 seconds or less;	
	 capable of local manual closing and remotely controlled closing; if transferring flammable LHG: 	
	= have fusible elements that melt at < 105C (221F) and activate emergency shutdown, or	
	 = have a sensor that perfroms the same function. - remote actuator for each valve: 	
	= accessible;= at least 15 meters (49.2 ft) from terminal manifold or loading arm:	
	= conspicuously marked; = automatically shuts down pumps or compressors used in	
	transfer.	
11. []	Warning Alarms 127.1207	
	 rotating or flashing amber light visible for at least 1 mile in all directions. 	
	- siren audible for at least 1 mile in all directions.	
	- obstruction?	

- additional or alternative warning devices?

12. []	Respiratory Protection 127.1209	Remarks
	- transfers one or more of the following: [] yes [] no - anhydrous ammonia;	
	- chlorine;	
	- dimethylamine;- ethylene oxide;	
	- methyl bromide; - sulphur dioxide;	
	- vinyl chloride;	
	if yes, then:	
	 provided for each employee in marine transfer area for LHG; protects wearer for at least 5 minutes. 	
13. []	Persons in Charge of Transfers for the Facility:	
	Qualifications and Certification 127.1301	
	- 48 hours transfer experience with each LHG transferred.	
	- knows hazards of each LHG transferred.	
	- knows rules of 33 CFR 127 subpart C.	
	- knows procedures in Ops and Emergency Manuals.	
	certification:in writing;	
	- current copy available for inspection at facility.	
14. []	Training 127.1302	
	- required subjects for PICs:	
	- properties and hazards of each LHG transferred;	
	use of gas detectors;use of respiratory protection equipment;	
	- basic firefighting procedures	
	 Ops and Emergency Manuals configuration and limitations of cargo systems of LHG vessels; 	
	 procedures for transferring to/from LHG vessels; 	
	 response procedures for a release handled by facility; first aid for burns, CPR, exposure to toxic LHG, and transport to 	
	medical facility; - restrictions on access to transfer area.	
	- refresher training for PICs at least every 5 years.	
	- record of training:	
	- for each person trained;	
	- retained for duration of employment + 12 months.	
15. []	Operations Manual 127.1305	
	- description of each liquid and vapor transfer system including:	
	mooring areas;transfer connection;	
	- control room (where installed); - diagram of piping and electrical systems.	

	- duties of each person assigned to transfers.	Remarks
	- maximum relief-valve setting or MAWP of transfer system.	
	- maximum relief-valve setting of waver of transfer system.	
	telephone numbers:supervisors;	
	- PICs for facility;	
	- persons on watch in marine transfer area for LHG;	
	- security personnel of the facility.	
	- description of security systems.	
	description of training programs	
	- description of training programs.	
	- procedures for security violations.	
	- transfer procedures for each LHG handled:	
	- requirements for each aspect of transfer:	
	= start-up,	
	= guaging, = cooldown,	
	= pumping,	
	= venting,	
	= shutdown.	
	- maximum transfer rate;	
	 minimum transfer temperature; firefighting equipment requirements; 	
	- communications procedures.	
16. []	Emergency Manual 127.1307	
	- for each LHG handled:	
	- physical description;	
	- description of hazards;	
	first aid procedures;response procedures for a release;	
	- if flammable, fire fighting procedures.	
	 emergency shutdown: description of emergency shutdown system; 	
	- procedures for emergency shutdown.	
	 fire equipment: description of the number, kind, place and use of fire equipment; 	
	- description of the number, kind, place and use of me equipment, - description of the number, kind, place and use of portable fire	
	extinguishers.	
	- telephone numbers:	
	- local Coast Guard units;	
	- hospitals;	
	fire departments;police departments;	
	- other emergency response organizations.	
	- location and provisions of personnel shelters.	
	- location of each first aid station.	
	- emergency procedures for mooring and unmooring a vessel.	
	2 - 2 - 2 - 1 - 2 - 2 - 2 - 2 - 2 - 2 -	

	- if off-site organization provides emergency response, copy of	Remarks
	written agreement.	
17. []	Motor Vehicles 127.1311	
	- parked only in designated parking space.	
	- no refueling in transfer area.	
	- no operation of vehicle/mobile equipment constituting an ignition	
	source within 15 meters (49.2 ft) of: - storage containers;	
	- manifolds; - loading arms;	
	- independent mating flange.	
	- designated parking spaces: - do not block fire lanes;	
	- do not impede entrances/exits;	
	 not located within 15 meters (49.2 ft) of any storage container, manifold, loading arm, or independent mating flange containing 	
	flammable liquid or gas.	
18. []	Storage of Hazardous Materials 127.1313	
	- only the following materials stored in marine transfer area for LHG:	
	 the LHG being transferred; fuel required by vessel or emergency response equipment in 	
	area;	
	- oily wastes received from vessels;	
	 solvents, lubricants, paints, and similar materials in the amount required for one day's operations and maintenance. 	
	- flammable liquids not stored in bulk are stored IAW Chapter 4,	
	NFPA 30.	
19. []	Declaration of Inspection 127.1317(e)	
	- signed copy of declaration of inspection available at the facility for	
	all transfers within last 30 days.	
	- declaration of inspection contains:	
	 name of vessel and facility; date and time the transfer begins; 	
	 list of requirements in 127.1315 and initials of both PICs after each requirement; 	
	 signatures of both PICs and date and time of signing; signature of each relief PIC and date and time of each relief. 	
20. []	Access to Marine Transfer Areas for LHG 127.1325	
	 access limited to: personnel who work in the area; 	
	- transfer personnel;	
	- vessel personnel;	
	 delivery and service personnel in the course of their business; Federal, state, and local officials; 	
	- other persons authorized by the operator	

	 each person allowed in the area is positively identified as someone authorized to enter. 	Remarks
	 each person, other than a facility employee has an identifying badge. 	
	- guards stationed and fences or other devices installed to respond to:	
	- unauthorized access;	
	- fires;	
	- release of LHG in the area.	
	- has COTP approved alternative to guards/security devices?	
	- operator allows access to facility for examination.	
21. []	Maintenance General 127.1401 thru 127.1409	
	- general (127.1401):	
	- all cargo handling equipment is operable and no equipment	
	that may cause the release or ignition of LHG is used in the marine transfer area for LHG.	
	- inspections (127.1403):	
	 visual inspection for defects of each pressure relief device not capable of being tested: 	
	= at least once every calendar year;	
	= intervals not exceeding 15 months.	
	- repairs (127.1405):	
	 equipment continues to meet applicable requirements; safety is not compromised; 	
	- welding and cutting meet NFPA 51B.	
	- tests (127.1407):	
	- static liquid-pressure test of LHG transfer system and	
	<pre>verification of set pressure of safety and relief valves:</pre>	
	= major repairs;	
	increase in the MAWP;at least once every calendar year with intervals not	
	exceeding 15 months.	
	- test of each pressure guage:	
	= conducted once each calendar year;	
	= interval does not exceed 15 months;	
	= displayed pressure is within 10% of actual pressure.	
	- test of each remote operating or indicating equipment:	
	= conducted at least once a year;= interval not to exceed 15 months.	
	tect of amarganay chutdown:	
	test of emergency shutdown:at least once every 2 months;	
	= at least once every 2 months, = if transfer occurs less than every 2 months, then before each transfer.	

	- test of warning alarms:	Remarks
	= at least once every 6 months;	
	= if transfer occurs less than every 6 months, then before	·
	each transfer.	
	- records (127.1409):	
	 desription of components inspected or tested under 127.1403 or 127.1407; 	·
	- date and results of each inspection or test;	
	 description of any repairs; date and description of each alteration or major repair; 	
	- information kept on file at least 24 months after inspection, test,	
	alteration or major repair.	
22. []	Firefighting Equipment 127.1501 thru 127.1511	
	- general (127.1501): - evaluation for firefighting equipment submitted to COTP with	
	emergency manual;	
	 equipment adequately maintained, periodically inspected and tested; 	
	- the following painted red or other conspicuous color and readily	
	accessable: = hydrants and standpipes;	
	= hose stations;	
	<pre>= portable fire extinguishers; = fire monitors:</pre>	
	- equipment bears approval, if applicable, of independent	· · · · · · · · · · · · · · · · · · ·
	laboratory recognized by NFPA.	
	- portable fire extinguishers (127.1503):	
	- of appropriate number size, and kind IAW NFPA 10.	
	- emergency response and rescue (127.1505):	
	 emergency response and rescue arranged; if by facility personnel: furnished appropriate training 	
	and equipment;	
	- if by off-site organization, then written agreement indicating:	
	services it will perform;time within which it will perform them.	
	= une within which it will perform them.	
	- water systems for fire protection (127.1507):	
	 water supply; means of distributing and applying water to: 	
	= protect personnel;	
	= cool storage tanks, equipment, piping, and vessels;	
	= control unignited leaks and spills in transfer area.	
	- on pier or wharf:	
	= one 2 1/2 in supply line;	
	= one 2 1/2 in fire hydrant;	
	enough 2 1/2 in fire hose to connect hydrant to vessel.each water system must simultaneously supply:	
	= all fixed fire protection systems at their design flow and	
	pressure for the worst single incident forseeable;	
	= 63 L/s (1000 gpm) for streams from hand-held hoses;	
	= for at least 2 hrs.	

 equipment for controlling and extinguishing fires (127.1509): portable or wheeled extinguishers suitable for gas fires available at strategic sites. 	
 international shore connection (127.1511): if receives foreign flag vessels, has international shore connection meeting ASTM F-1121. 	
23. [] Fire Protection 127.1601 thru 127.1605	
 smoking (127.1601): no smoking in marine transfer area for LHG unless neither flammable LHG nor its vapors are present or the person is in a place designated and marked IAW local law. 	
- hotwork (127.1603): - permit from COTP?	
 other sources of ignition (127.1605): no open fires or open flame lamps; heating equipment will not ignite combustible material; spark arrestors installed where applicable; all rubbish, debris and waste in appropriate receptacles. 	

SECTION 4.

BULK LIQUID FACILITY INSPECTION (33 CFR 154 and 156)

A.	<u>G</u> E	NE	<u>ERAL</u>	Remarks
1.	[]	Alternatives 154.107 and 156.107	
			 conduct a file review for COTP approved alternatives to the regulations. Ensure compliance. Facility copy readily available. 	
2.	[]	Exemptions 154.108 and 156.110	
			 conduct a file review of COMDT approved exemptions to the regulations. Ensure compliance. Facility copy readily available. 	
3.	[]	Letter of Intent 154.110 and 154.740	
			- written notice of changes.	
			- cancelled in writing if operations no longer conducted.	
			- copy available at facility.	
4.	[]	Facility Examination 154.120	
			- operator allowing examination.	
			- performing tests for compliance.	
В.	<u>OF</u>	PEF	RATIONS MANUAL	
1.	[]	General 154.300	
			- manual current.	
			- readily available for COTP examination.	
			- readily available for PIC of transfers.	
			- includes translations into languages understood by all PICs of the facility.	
			- responsibilities of transfer personnel per 154 and 156.	
2.	[]	Contents 154.310	
			- ensure that the facility operation is accurately depicted by the Operations Manual.	
			- geographic location	

- physical description still current:	Remarks
- mooring areas;	
- wharfs;	
- transfer locations;	
- control stations;	
- safety equipment locations;	
 boundaries of Coast Guard jurisdiction; extent and scope of piping subject to tests required by 	
156.170(c)(4).	
100.170(0)(4).	
- hours of operation.	
- sizes, types, and number of vessels permitted to transfer	
simultaneously.	
- for each of the products transferred:	
- generic/chemical name;	
- shipping name;	
- description:	
= appearance;	
= odor;	
= hazards.	
 instructions for safe handling; procedures for spill/leak or personnel exposure; 	
- firefighting procedures & effective extinguishing agents.	
mongraming processarios at checano oxamigationing agorito.	
- minimum number of persons on duty during transfers.	
- list of emergency phone numbers:	
- facility personnel;	
- Coast Guard; - other.	
- duties of watchman for unmanned vessels moored at the facility	
(33 CFR 155.810 and 46 CFR 35.05-15).	
- description of communications system.	
- location/description of personnel shelters, if any.	
- location/description of personner shelters, if any.	
- drip/discharge collection and vessel slop reception facilities	
description and instructions.	
- emergency shutdowns - description and location.	
- monitoring devices, if required by 154.525:	
- mornioring devices, in required by 154.525 quantity;	
- types;	
- location;	
- instructions for use.	
- containment equipment required by 154.545:	
- quantity;- type;	
- type, - location;	
- instructions for use;	
- time limits for access.	

			- fire extinguishing equipment required by 154.735(d):	Remarks
			- quantity;	
			- type;	
			- location;	
			- instructions for use.	
			- MAWP of each loading arm, transfer pipe system, and hose assembly required to be tested by 156.170, including maximum	
			relief valve setting (or maximum system pressure when relief valves not provided) for each transfer system.	
			- tank cleaning or stripping operations description if facility cleans or	
			strips tanks.	
			- procedures:	
			 loading arm operations/limitations; 	
			- transferring oil or HAZMAT;	·
			- completion of pumping;	
			- emergencies;	
			- reporting/initial containment of discharges.	
			- brief summary of applicable Federal, state, and local oil/HAZMAT	
			pollution laws/regulations.	
			- procedures for shielding portable lighting, if authorized by COTP.	
			- description of training/qualification program for PICs.	
			- statement explaining each transfer hose is either:	
			- marked with name of each product it handles;	
			 marked with symbol and location in OPS manual where compatibility list may be found. 	
			454 040(h) 1/1 - 1	
			 vapor control system description, per 154.310(b) if facility collects vapors. 	
			- manual written in order per 154.310(a) or has cross-referenced	
			index page.	
3.	[]	Manual Amendments 154.320	
			- all approved amendments incorporated in manual per 154.310(c).	
4.	[]	Examination by the Coast Guard 154.325	
			- manual marked "Examined by the Coast Guard."	
C.	<u>TR</u>	<u>AN</u>	NSFER EQUIPMENT REQUIREMENTS	
1.	[]	Transfer Hose: Design and Markings 154.500	
			- minimum burst pressure per 154.500(a).	
			- MAWP per 154.500(b).	
			- nonmetallic hoses usable for oil or hazardous material service.	

		- proper connections (must be one of the following):	Remarks
		- fully threaded;	
		- flanges meet ANSI Standard B16.5 or ANSI Standard B16.24;	
		- quick-disconnect couplings meet ASTM F-1122.	
		- markings or records:	
		 name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; 	
		- MAWP;	
		- date of manufacture;	
		date of last test;burst and test pressure recorded (not on hose).	
		- buist and test pressure recorded (not on nose).	
		 automatic backpressure shut-off nozzles, if necessary for hose used for fuel transfers. 	
2.	[]	Transfer Hose: Tests & Conditions 156.170	
		- no unrepaired kinks, bulges, soft spots, loose covers, other defects.	
		- no cuts, slashes, or gouges that penetrate the first layer of hose	
		reinforcement.	
		- no external/internal deterioration.	
		 annually tested at 1.5 MAWP, does not burst, bulge, leak or abnormally distort. 	
		- record test info in Physical Info (Section 10, Part I)	
3.	[]	Loading Arms: Design & Markings 154.510	
		- meets ANSI B31.3 (for those placed in service after 30 Jun 73).	
		 manufacturer's certification permanently marked or recorded elsewhere. 	
		- means of draining or closing before disconnect.	
4.	[]	Loading Arms: Tests & Conditions 156.170	
		 no defects that would permit the discharge of oil or hazardous material. 	
		- annually tested at 1.5 MAWP, does not leak.	
		- record test into Physical Info (Section 8, Part I)	
5.	[]	Transfer Pipe System 156.170	
		 no defects that would permit the discharge of oil or hazardous material. 	
		- annually tested at 1.5 MAWP, or approved alternative; does not leak.	

			 extent of pipe test: to first valve inside SPCC area, other approved procedure? Exp 		Remarks
			- record test info in Physical Info (Se	ection 8, Part I)	
6.	[]	Transfer System Relief Val Valves 156.170	ves and Pressure	
			- TSRVs open at or below pressure	setting.	
			- pressure gauges show pressure w	ithin 10% of actual pressure.	
			- record test info in Physical Info (Se	ection 8, Part I)	
7.	[]	Emergency Shutdown, Rei Tank Level Alarms 156.		
			- operating properly.		
			- record tests info in Physical Info (S	Section 8, Part I).	
8.	[]	Closure Devices 154.520		
			enough to blank off ends of each h connected for transfer (new, unus cleaned and gas freed are exer	sed hose and hose that has been	
9.	[]	Monitoring Devices 154.	525	
			- required by COTP? [] yes	[] no	
			- operational.		
10.	[]	Small Discharge Containm	ent 154.530	
			 required at each: handling or loading arm area. hose connection manifold. each hose connection during confixed or portable). 	upling, uncoupling, and transfer	
			- capacity required.		
			hose/loading arm diameter (in)	fixed capacity required	
			1.0 - 6.0 6.1 - 11.9	2 BBLS 3 BBLS	
			12 +	4 BBLS	
			if COTP finds above not practical	1/2 BBL (portable)	
11.	[]	Small Discharge Removal	154.540	
			- means to safely remove within 1 h	our without discharge into water.	

12. []	Discharge Containment Equipment for Oil &	Remarks
- -	Hazardous Liquids 154.545	
	- booming required for oil or hazmat transfer?	
	- IF OIL FACILITY SEE PART F, OIL SPILL RESPONSE PLANS, IF HAZARDOUS LIQUIDS FACILITY CONTINUE.	
	- adequate amount of equipment.	
	- "ready access" established through: - direct ownership;	
	- joint ownership; - CO-OP or OSRO membership;	
	- contractual agreement.	
	- compare with Ops manual for required amounts and access.	
	- time limits for deployment.	
	- condition of equipment stored at facility, if any.	
13. []	Emergency Shutdown 154.550	
	 enables vessel PIC to stop flow from facility to vessel, or direct facility to do same. 	
	- note type in remarks, and who controls	
	 electric, pneumatic, or mechanical link to facility; electronic voice communication system continuously operated. 	
	- near dock manifold connection.	
	- meets time requirements;	
	- oil facility:= operating after 1 Nov 80: 30 seconds;	
	= operating on or before 1 Nov 80: 60 seconds; - hazardous liquid facility:	
	= operating on or after 4 Oct 90: 30 seconds; = operating before 4 Oct 90: 60 seconds.	
44 . 1		
14. []	Communications 154.560	
	 continuous two-way voice communication bewteen vessel and facility PICs. 	
	- means to signal use of communications.	
	- usable in all conditions of weather and operations.	
	- portable radios:	
	 marked or documented as intrinsically safe; certified as intrinsically safe by national testing lab or certification 	
	organization recognized by COMDT.	
	- test communications, record results in remarks.	

15. []	Lighting 154.57	0	Remarks	
	- transfer operations	n sunrise and sunset, fixed lighting a work areas for facility and vessel; points for facility and vessel.	<u> </u>	
	- located or shielded to pavigation.	prevent interference/confusion with		
	- adequate. If not, COT remarks.	P request verification, record results	in	
	- provided by vessel or p	portable approved by COTP?		
D. <u>VAP</u>	OR CONTROL SYS	TEMS		
1. []	VCS Certification	154.804		
	- system installed d	late:		
	- certification		date:	
	- initial inspection d	late:		
	- certify entity n	name:		
	а	address:		
2. []	VCS Testing 15	6.170		
	- following equipment te	ested/inspected annually:		
	- hoses	date:		
	- relief valve	date:		
	- pressure valve	date:		
	- loading arms	date:		
	- piping system	date:		
	- pressure sensor	date:		
	- remote operating or			
	remote operating or	date:		
	- arrestore - inenected in	nternally within last year:		_
	- detonation arrestors			_
	 flame arrestors 	date:		

	- analyzers - calibrated within previous 2 weeks or 24 hours:	Remarks
	- hydrocarbon analyzer: [] yes	
	- oxygen analyzers: [] yes	
F FACII	LITY OPERATIONS	
1. []	PIC Designation/Qualification 154.710, 154.730 and 154.740(b)	
	and 154.740(b)	
	- designated by facility operator.	
	experience:at least 48 hours in transfer operations;adequate experience at current facility.	
	- review operations manual for training requirements.	
	- has certification of completion of required training.	
	- evidence of designation carried or immediately available at facility.	
	- record of each person currently designated as Person in Charge.	
2 []	PIC Limitation Exemption 156.115	
	 PIC authorized by COTP to be PIC for both facility and vessel during transfer operations? 	
	[] yes (explain in remarks) [] no	
3. []	Are Transfer Notifications Made if Required by 156.118	
	[] yes	
4. []	Records Available 154.740	
	- letter of intent	
	- declaration of inspection:	
	 available for all transfers within last 30 days; signed only by PICs listed in facility's current record of PIC 	
	under 154.740; - properly completed with following information:	
	= name of vessel and facility;	
	<pre>= address/location of transfer; = date transfer started:</pre>	
	= list of requirements per 156.120;	
	= date/time of signing, signature/title of all PICs involved in transfer.	
	- date and result of most recent test or examination under 156.170.	
	- hose information required under 154.500(e) and (g).	
	- record of all COTP examinations within last 3 vrs.	

			- documentation that portable radios are intrinsically safe, if not so	Remarks
			marked.	
			- material safety data sheet for each product transferred at facility.	
			vapor control system:record of all automatic shutdowns within last 3 yrs;plans, calculations, and specifications of system.	
5.	[1	Access 154.735(a)	
			- access for emergency equipment not impeded.	
6.	[]	Hazardous Stores & Supplies 154.735(b)	
			- only in amounts necessary for operations maintenance, properly stored.	
7.	[]	Gasoline or Other Fuel 154.735(c)	·
			- not stored on pier, wharf, or other similar structure.	
8.	[]	Fire Extinguishers 154.735(d)	
			- sufficient number.	
			- approved by independent laboratory.	
			- maintained in ready condition.	
			- suitably located.	
9.	[1	Fire Fighting Equipment Location 154.735(e)	
			- conspicuously marked and readily accessible:	
			- hydrant; - standpipe;	
			- fire extinguisher; - fire alarm box.	
10.	г	1	Protective Equipment 154.735(f)	
10.	L	1		
	_		- ready to operate.	
11.	[]	Smoking 154.735(g) and 154.735(u)	
			- "No Smoking" signs conspicuously posted.	
			 designated smoking areas in compliance with local ordinances and regulations. 	
			- signs marking authorized smoking areas conspicuously posted.	
12.	[]	Vehicles 154.735(h)	
			- trucks and vehicles parked or operated only in designated areas.	

13.	[]	Rubbish 154.735(I) Rer	narks
			- kept in receptacles.	
14.	[]	Internal Combustion Engine Equipment 154.735(j)	
			- not a fire hazard.	
			- approved fire extinguisher attached, unless one readily nearby.	
15.	[]	Spark Arresters 154.735(k)	
			- provided on all chimneys or appliances that: - use solid fuel; - are a hazard to nearby combustible material.	
16.	[]	Welding/Hot Work 154.735(I)	
			- conducted IAW NFPA 51B.	
			- notification of the COTP required?	
17.	[]	Heating Equipment 154.735(m)	
			- has sufficient clearance.	
18.	[]	Automotive Equipment with ICE 154.735(n)	
			- not refueled on pier or wharf.	
19.	[]	Fires and Flame Lamps 154.735(o)	
			- no open fires or flame lamps	
20.	[]	Electrical Wiring and Equipment 154.735(p), 154.735(q) and 154.735(r)	
			- maintained in safe condition to prevent fires.	
			- if installed after 4 Oct 90: - meets NFPA 70;	
			- shows approval for use by: = underwriters laboratories;	
			= Factory Mutual Research Corp.;	
	_	_	= Canadian Standards Association.	
22.	[]	Tank Cleaning/Gas Freeing Operations 154.735(s)	
			- IAW ISGOTT	

23. []	Security Guards or Equivalent Controls 154.735(t)	Remarks
	- prevent lawful access.	
	- detect fires.	
	- report emergencies.	
24. []	Warning Signs 154.735(v)	
	- posted at point of transfer, without obstruction.	
	- conform to 46 CFR 151.45-2(E)(1) or 153.955.	
F. OIL S	SPILL RESPONSE PLANS	<u>.</u>
1. []		
[]		
	- plan submitted.	
	- operating in compliance with plan after 18 Aug 93.	
	- contracts under plan still valid.	
	- plan reapproved by COTP every 5 yrs.	
2. []	Qualified Individual & Alternate 154.1026	
	- QIC Name:	
	- Alternate Name:	
	- designation documents.	
3. []	Method of Ensuring Availability of Response Resources 154.1028	
	- OSRO Contract? Date:	
	- name of OSRO:	
	- effective period of contract:	
	- facility self-certification? Date:	
	- OSRO membership document? Date:	
	- name of OSRO:	
	- other OSRO document? Date:	
	- name of OSRO:	
	- acknowledges intent to commit resources;	
	 permits CG verification; referenced in response plan. 	

		- OSRO identified in response plan?	Remarks
		- name of OSRO:	
		- all applicable contracts and documents list above: - retained at facility; - available for review.	
4. [MTR (NTR) Discharge Scenarios 154.1029 and 154.1035	
		- MTR AMP discharge:BBLS	
		- MTR MMP discharge: BBLS	
		- MTR worst case:BBLS	
		- NTR worst case:BBLS	
		- consistent with criteria in 154.1029? [] yes [] no	
5. []	Sensitive Areas Indentified in the ACP 154.1035	
		- list:	
		- (2)	
		- (3)	
		- (4)	
		<u>-</u>	
6. <u>[</u>	J	Response Resources Identified 154.1045	
		resources for AMP discharge:containment deployable within 1 hour;	
		 recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. 	
		- resources for MMP discharge:	
		- high volume: = Great Lakes ports: available on scene in 6 hours.	
		= other ports: available on scene in 12 hours sufficient transport/deployment equipment.	
		- resources for worst case discharge:	
		- TAPAA facility: equipment required on scene under 3 tier system.	
		- non-TAPAA facility: equipment required on scene per 3 tier system.	
		- sufficient transport/deployment equipment.	
		- list major response equipment for AMP/MMP in Physical Info Sect.	

7.	[]	Training 154.1050 F	Remarks
			- record of response training maintained and available.	
			- retained for 3 years.	
8.	[1	Drills 154.1055	
			- monthly notifications drills; dates:	
			- semi-annual equipment deployment drills; dates:	
			- annual tabletop drills; dates:	
			- annual unannounced drill; dates:	
			- retain records for 3 years.	
9.	[]	Inspection/Maintenance of Non-OSRO Resources 154.1057	
			154.1057	
			 major equipment periodically inspected and maintained in good operating condition. 	
			- records of inspection/maintenance available.	
			- records retained for 3 years.	
			- COTP verification of on-site equipment: - inventory verified: - records verified: - condition of equipment verified: - inspection/operational test performed: [] yes [] no - inspection/operational test performed: [] yes [] no	
			if no;	
			- COTP verification of OSRO equipment: - last inspection of OSRO; date:	
10.	[]		
			Response Equipment for AMP/MMP Discharge	
			- boom	
			- skimmers	
			- tow capable boats/engines h.p.	
			- note date in Physical Info Section.	
11.	[]	Plan Approved by COTP 154.1060	
			- copy available to owner/operator.	
			- copy available to qualified individual.	
			- retained records for 3 years.	

12. []	Annual Review by Owner/Operator 154.1065	Remarks
	- annual letters/amendments included with copy of plan.	
	- changes entered in plan and noted in "Record of Changes."	
	- dates of annual letters/amendments; dates:	
	- plan revisions required per 154.1065(b).	

SECTION 5.

MOBILE BULK LIQUID FACILITY INSPECTION (33 CFR 154 and 156)

A.	<u>G</u> E	ENI	<u>ERAL</u>	Remarks
1.	[]	Alternatives 154.107 and 156.107	
			 conduct a file review for COTP approved alternatives to the regulations. Ensure compliance. Facility copy readily available. 	
2.	[]	Exemptions 154.108 and 156.110	
			 conduct a file review of COMDT approved exemptions to the regulations. Ensure compliance. Facility copy readily available. 	
3.	[1	Letter of Intent 154.110 and 154.740	
			- written notice of changes.	
			- cancelled in writing if operations no longer conducted.	
			- copy available at facility.	
4.	[]	Facility Examination 154.120	
			- operator allowing examination.	
			- performing tests for compliance.	
В.	<u>OF</u>	PEF	RATIONS MANUAL	
1.	[]	General 154.300	
			- manual current.	
			- readily available for COTP examination.	
			- readily available for PIC of transfers.	
			 includes translations into languages understood by all PICs of the facility. 	
			- responsibilities of transfer personnel per 154 and 156.	
2.	[]	Contents 154.310	
			- ensure that the facility operation is accurately depicted by the	

- physical description still current:	Remarks
- transfer locations;	
- control stations;	
- safety equipment locations;	
- boundaries of Coast Guard jurisdiction;	
- extent and scope of piping subject to tests required by	
156.170(c)(4).	·
- hours of operation.	
 sizes, types, and number of vessels permitted to transfer simultaneously. 	
Silituitarieousiy.	
- for each of the products transferred:	
- generic/chemical name;	
- shipping name;	
- description:	
= appearance;	
= odor; = hazards.	
= nazarus instructions for safe handling;	
- instructions for safe framing, - procedures for spill/leak or personnel exposure;	
- firefighting procedures & effective extinguishing agents.	
mongraing procedures a shooting examining agenter	
- minimum number of persons on duty during transfers.	
 list of emergency phone numbers: facility personnel; 	
- Coast Guard;	
- other.	
- description of communications system.	
- emergency shutdowns - description and location.	
- containment equipment required by 154.545:	
- quantity;	
- type;	
- location;	
- instructions for use;	
- time limits for access.	
fire outing linking agricement required by 154 705/d/v	
 fire extinguishing equipment required by 154.735(d): quantity; 	·
- type;	
- location;	
- instructions for use.	
- MAWP of each loading arm, transfer pipe system, and hose	
assembly required to be tested by 156.170, including maximum	
relief valve setting (or maximum system pressure when relief valves not provided) for each transfer system.	
valves not provided, for each transfer system.	
- tank cleaning or stripping operations description if facility cleans or	
strips tanks	

			- procedures:	Remarks
			- loading arm operations/limitations;	
			- transferring oil or HAZMAT;	·
			- completion of pumping;	
			- emergencies;	
			- reporting/initial containment of discharges.	
			- procedures for shielding portable lighting, if authorized by COTP.	
			- description of training/qualification program for PICs.	
			- statement explaining each transfer hose is either:	
			 marked with name of each product it handles; marked with symbol and location in OPS manual where compatibility 	
			list may be found.	
			iist may be lound.	
			 manual written in order per 154.310(a) or has cross-referenced index page. 	
3.	Г	1	Manual Amendments 154.320	
	١.	,	mandal / mondification to 10-10-20	
			- all approved amendments incorporated in manual per 154.310(c).	
4.	[]	Examination by the Coast Guard 154.325	
			- manual marked "Examined by the Coast Guard."	
C. <u>T</u>	ſR	A١	ISFER EQUIPMENT REQUIREMENTS	
1.	[]	Transfer Hose: Design and Markings 154.500	
1.	[]	Transfer Hose: Design and Markings 154.500 - minimum burst pressure per 154.500(a).	
1.	[]	- minimum burst pressure per 154.500(a).	
1.	[]		
1.	[]	- minimum burst pressure per 154.500(a).	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; 	
1. 2.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; automatic backpressure shut-off nozzles, if necessary for hose 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; automatic backpressure shut-off nozzles, if necessary for hose used for fuel transfers. Transfer Hose: Tests & Conditions 156.170 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; automatic backpressure shut-off nozzles, if necessary for hose used for fuel transfers. 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; automatic backpressure shut-off nozzles, if necessary for hose used for fuel transfers. Transfer Hose: Tests & Conditions 156.170 no unrepaired kinks, bulges, soft spots, loose covers, other defects. 	
1.	[]	 minimum burst pressure per 154.500(a). MAWP per 154.500(b). nonmetallic hoses usable for oil or hazardous material service. proper connections (must be one of the following): fully threaded; flanges meet ANSI Standard B16.5 or ANSI Standard B16.24; quick-disconnect couplings meet ASTM F-1122. markings or records: name of product handled, "OIL SERVICE", or "HAZMAT SERVICE - SEE LIST" followed by symbol; automatic backpressure shut-off nozzles, if necessary for hose used for fuel transfers. Transfer Hose: Tests & Conditions 156.170 no unrepaired kinks, bulges, soft spots, loose covers, other 	

			 annually tested at 1.5 MAWP, does not burst, bulge, leak or abnormally distort. 	Remarks
			- record test info in Physical Info (Section 8, Part I)	
			(2000-00-00-00-00-00-00-00-00-00-00-00-00	
3.	[]	Transfer System Relief Valves and Pressure Valves 156.170	
			- TSRVs open at or below pressure setting.	
			- pressure gauges show pressure within 10% of actual pressure.	
			- record test info in Physical Info (Section 8, Part I)	
4.	[]	Emergency Shutdown, Remotely Operated Valves, Tank Level Alarms 156.170	
			- operating properly.	
			- record tests info in Physical Info (Section 8, Part I).	
5.	[]	Closure Devices 154.520	
			 enough to blank off ends of each hose and loading arm not connected for transfer (new, unused hose and hose that has been cleaned and gas freed are exempt). 	
6.	[]	Small Discharge Containment 154.530	
			required at each:handling or loading arm area.hose connection manifold.	
			- capacity - not less than 5 gallons.	
7.	[]	Discharge Containment Equipment for Oil & Hazardous Liquids 154.545	
			- booming required for oil or hazmat transfer?	
			- IF OIL FACILITY SEE PART F, OIL SPILL RESPONSE PLANS, IF HAZARDOUS LIQUIDS FACILITY CONTINUE.	
			- adequate amount of equipment.	
			- "ready access" established through:	
			- direct ownership;	
			- joint ownership;- CO-OP or OSRO membership;	
			- contractual agreement.	
			- compare to Ops manual for required amounts and access.	
			- time limits for deployment.	
			- condition of equipment stored on facility, if any.	

8.	[]	Emergency Shutdown 154.5	50	Remarks
			enables vessel PIC to stop flow, from fa facility to do same.	cility to vessel, or direct	
			note type in remarks, and who controls electric, pneumatic, or mechanical lir electronic voice communication systems.		
			- near dock manifold connection.		
			 meets time requirements; oil facility: operating after 1 Nov 80: 30 see operating on or before 1 Nov 80 hazardous liquid facility: operating on or after 4 Oct 90: 3 	60 seconds;	
			= operating before 4 Oct 90: 60 s		
9.	[]	Communications 154.560		
			- continuous two-way voice communicati facility PICs.	on between vessel and	
			- means to signal use of communications	i.	
			- usable in all conditions of weather and	operations.	
			- portable radios: - marked or documented as intrinsical - certified as intrinsically safe by nation	nal testing lab or certification	
			organization recognized by COMD1		
			- test communications, record results in r	emarks.	
10.	[]	Lighting 154.570		
			 for operations between sunrise and sur transfer operations work areas for fa transfer connection points for facility 	cility and vessel;	
			 located or shielded to prevent interferent navigation. 		
			- adequate. If not, COTP request verification remarks.	ation, record results in	
			- provided by vessel or portable approve	d by COTP?	
D. [FΑ	CI	LITY OPERATIONS		
_	_	_		154 740 454 720	
1.	L	J	PIC Designation/Qualification and 154.740(b)	154.710, 154.730	
			- designated by facility operator		

			- experience:		
			Remarks at least 48 hours in transfer operations;		
			- adequate experience at current facility.	_	
			- review operations manual for training requirements.		
			- has certification of completion of required training.		_
			- evidence of designation carried or immediately available at facility.		
			- record of each person currently designated as Person in Charge.		
2	[]	PIC Limitation Exemption 156.115		
			 PIC authorized by COTP to be PIC for both facility and vessel during transfer operations? 		
			[] yes (explain in remarks) [] no		
_	_	_			
3.	[]	Are Transfer Notifications Made if Required by 156.118		
			[] yes		
4.	[]	Records Available 154.740		
			- letter of intent		
			- letter of intent		
			 declaration of inspection: available for all transfers within last 30 days; 		
			 signed only by PICs listed in facility's current record of PIC under 154.740; 		
			 properly completed with following information: name of vessel and facility; 		
			= address/location of transfer; = date transfer started;		
			= list of requirements per 156.120;		
			= date/time of signing, signature/title of all PICs involved in transfer.		
			- date and result of most recent test or examination under 156.170.		
			- hose information required under 154.500(e) and (g).	-	
			- record of all COTP examinations within last 3 yrs.		
			 documentation that portable radios are intrinsically safe, if not so marked. 		
			- material safety data sheet for each product transferred at facility.		
5.	[1	Access 154.735(a)		
			access for amarganey aguinment not impeded		

6.	[1	Fire Extinguishers 154.735(d)	Remarks
			- sufficient number.	
			- approved by independent laboratory.	
			- maintained in ready condition.	
			- suitably located.	
7	г	1	Protective Equipment 154.735(f)	
۲.	L	J		
			- ready to operate.	
8.	[]	Smoking 154.735(g)	
			- "No Smoking" signs conspicuously posted.	
9.	[]	Rubbish 154.735(I)	
			- kept in receptacles.	
10.	Г	1	Internal Combustion Engine Equipment	
	-	-	154.735(j)	
			- not a fire hazard.	
			- approved fire extinguisher attached, unless one readily nearby.	
11.	[]	Spark Arresters 154.735(k)	
			 provided on all chimneys or appliances that: use solid fuel; are a hazard to nearby combustible material. 	
12.	ſ	1	Heating Equipment 154.735(m)	
	٠	•		
			- has sufficient clearance.	
13.	[]	Fires and Flame Lamps 154.735(o)	
			- no open fires or flame lamps	
14.	[]	Electrical Wiring and Equipment 154.735(p), 154.735(q) and 154.735(r)	
			- maintained in safe condition to prevent fires.	
			- if installed after 4 Oct 90: - meets NFPA 70;	
			shows approval for use by:= underwriters laboratories;	
			= Factory Mutual Research Corp.; = Canadian Standards Association.	

15. []	Tank Cleaning/Gas Freeing Operations 154.735(s)	Remarks
			- IAW ISGOTT	
16. [1	Warning Signs 154.735(v)	
		•	- posted at point of transfer, without obstruction.	
			- conform to 46 CFR 151.45-2(E)(1) or 153.955.	
E. <u>O</u>	<u>IL</u>	S	SPILL RESPONSE PLANS	
1. []	Operating Restrictions 154.1025	
			- plan submitted.	
			- operating in compliance with plan after 18 Aug 93.	
			- contracts under plan still valid.	
			- plan reapproved by COTP every 5 yrs.	
2. []	Qualified Individual & Alternate 154.1026	
			- QIC Name:	
			- Alternate Name:	
			- desgnation documents.	
3. []	Method of Ensuring Availability of Response Resources 154.1028	
			- OSRO Contract? Date:	
			- name of OSRO:	
			- effective period of contract:	
			- facility self-certification? Date:	
			- OSRO membership document? Date:	
			- name of OSRO:	
			- other OSRO document? Date:	
			- name of OSRO:	
			 - acknowledges intent to commit resources; - permits CG verification; 	
			- referenced in response plan.	
			- OSRO identified in response plan?	
			- name of OSRO:	

			 all applicable contracts and documents list above: retained at facility; available for review. 	Remarks
4.	[]	MTR (NTR) Discharge Scenarios 154.1029 and 154.1035	
			- MTR AMP discharge:BBLS	
			- MTR MMP discharge: BBLS	
			- MTR worst case: BBLS	
			- NTR worst case:BBLS	
			- consistent with criteria in 154.1029? [] yes [] no	
5.	[]	Sensitive Areas Indentified in the ACP 154.1035	
			- list:	
			- (1)	
			- (2)	
			- (3)	
			- (4)	
_	г	1	Response Resources Identified 154.1045	
D.			NESDONSE NESDONCES IDENTINED 134.1043	
о.	L	,	·	
ο.	L	•	- resources for AMP discharge:	
ο.	L	,	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; 	
о.	L	,	- resources for AMP discharge: - containment deployable within 1 hour;	
о.	L	,	- resources for AMP discharge: - containment deployable within 1 hour; - recovery/storage equipment available on scene in 2 hours; - sufficient transport/deployment equipment. - resources for MMP discharge:	
о.	L	•	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: 	
0.	L		 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: Great Lakes ports: available on scene in 6 hours. other ports: available on scene in 12 hours. 	
0.	ı	•	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: Great Lakes ports: available on scene in 6 hours. 	
0.	ı	•	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: Great Lakes ports: available on scene in 6 hours. other ports: available on scene in 12 hours. sufficient tranpsort/deployment equipment. resources for worst case discharge: 	
0.		•	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume:	
0.		•	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume:	
0.		,	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume:	
0.		,	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume:	
7.	Γ	1	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: Great Lakes ports: available on scene in 6 hours. other ports: available on scene in 12 hours. sufficient tranpsort/deployment equipment. resources for worst case discharge: TAPAA facility: equipment required on scene under 3 tier system. non-TAPAA facility: equipment required on scene per 3 tier system. sufficient transport/deployment equipment. list major response equipment for AMP/MMP in Physical Info Sect. 	
7.	[]	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: Great Lakes ports: available on scene in 6 hours. other ports: available on scene in 12 hours. sufficient tranpsort/deployment equipment. resources for worst case discharge: TAPAA facility: equipment required on scene under 3 tier system. non-TAPAA facility: equipment required on scene per 3 tier system. sufficient transport/deployment equipment. list major response equipment for AMP/MMP in Physical Info Sect. 	
7.	[]	 resources for AMP discharge: containment deployable within 1 hour; recovery/storage equipment available on scene in 2 hours; sufficient transport/deployment equipment. resources for MMP discharge: high volume: Great Lakes ports: available on scene in 6 hours. other ports: available on scene in 12 hours. sufficient transport/deployment equipment. resources for worst case discharge: TAPAA facility: equipment required on scene under 3 tier system. non-TAPAA facility: equipment required on scene per 3 tier system. sufficient transport/deployment equipment. list major response equipment for AMP/MMP in Physical Info Sect. Training 154.1050	

8.	[]	Drills 154.1055	Remarks
			- monthly notifications drills; dates:	
			- semi-annual equipment deployment drills;dates:	
			- annual tabletop drills; dates:	
			- annual unannounced drill; dates:	
			- retain records for 3 years.	
9.	[]	Inspection/Maintenance of Non-OSRO Resources 154.1057	
			 major equipment periodically inspected and maintained in good operating condition. 	
			- records of inspection/maintenance available.	
			- records retained for 3 years.	
			- COTP verification of on-site equipment: - inventory verified: - records verified: - condition of equipment verified: - inspection/operational test performed:	[] yes [] no
			if no;	
			- COTP verification of OSRO equipment: - last inspection of OSRO; date:	
10.	[]	Date of Most Recent Inspection of Major Response Equipment for AMP/MMP Discharge	
			- boom	
			- skimmers	
			- tow capable boats/engines h.p.	
			- note date in Physical Info Section.	
11.	[]	Plan Approved by COTP 154.1060	
			- copy available to owner/operator.	
			- copy available to qualified individual.	
			- retained records for 3 years.	
12.	[]	Annual Review by Owner/Operator 154.1065	
			- annual letters/amendments included with copy of plan.	
			- changes entered in plan and noted in "Record of Changes."	
			- dates of annual letters/amendments; dates:	
			- plan revisions required per 154.1065(b).	

SECTION 6.

MARPOL RECEPTION FACILITY INSPECTION (33 CFR 158)

A. <u>C</u>	jΕ	NE	ERAL REQUIREMENTS	Remarks
1.	[]	Applicability 158.110 and 158.133	
			- oil [] yes [] no	
			- NLS [] yes [] no	
			- garbage [] yes [] no	
2.]]	COAs Required 158.135	
			- oil [] yes [] no	
			- NLS [] yes [] no	
			- garbage [] yes [] no	
3.	[]	Application for COA 158.140	
			- oil date:	
			- NLS date:	
			- garbage date:	
4.	[]	Waivers and Alternatives 158.150	
			- letter of application date:	
			- COTP waiver letter date:	
5.	[]	Termination of COA 158.160 and 158.170	
			- reason (suspended, revoked, not applicable)	
			- COTP letter date:	
6.	[]	Reception Facility Operation 158.163	
			- full compliance.	
			- copy of COA must be:	
			- at port or terminal;- available for inspection;	
			- attached to operations manual.	
7.	[]	COA Change of Information 158.165	
			- notification in writing & within proper time frames.	
			- copy of notification maintained at port or terminal until corrected COA issued.	

B.	<u>0</u>	IL)	Y MIXTURES AND RESIDUES	Remarks
1.	[]	General 158.200	
			- holds all required local, state and Federal permits.	
			- receive within 24 hours notice.	
			- complete transfer of oily ballast in less than 10 hours.	
			- complete transfer of oily mixtures in less than 4 hours.	
			- exception for ship repair yards.	
2.	[]	Crude Oil 158.210	
			- capacities: - sludge from fuel and L/O processing:	
			- oily bilge water:	
			- oily ballast:	
3.	[1	Oil Other Than Crude or Bunkers (more than	
	-	_	1000 metric tons) 158.220	
			- capacities: - sludge from fuel & L/O processing:	
			- oily bilge water:	
			- oily ballast:	
			- cargo residue:	
4.	[]	Barge Termnals and Others 158.230	
			- capacities: - sludge:	
			- oily bilge water:	
5	г	1	Ship Repair Yards 154.240	
٠.	•	,	- capacities:	
			- ballast water:	
			- oily solids:	
			- oily ballast:	
			- cargo residue:	
6.	[]	Standard Discharge Connection 158.250	
			- meets 33 CFR 155.430.	
			- attaches to each hilde hose or nine	

C.	N	O	KIOUS LIQUID SUBSTANCES	Remarks
1.	[]	General 158.310	
			- holds all required local, state, and Federal permits.	
			- receive within 24 hours of notice.	
			- complete NLS transfer in less than 10 hours.	
			- ship repair yard exception.	
2.	[]	Capacity & Exceptions 158.320	
			- category A capacities: - solidifying:	
			- non-solidifying:	
			- exception for handling only Category B or C:	
			- ship repair yard capacity:	
3.	[]	Equipment, Ports & Terminals 158.330	
			- capable of NLS transfer at mean low tide.	
			- instruction manual.	
D.	<u>G</u>	ΑF	RBAGE	
1.	Г	1	General 158.410	
	٠	•	- receive within 24 hours of notice (APHIS regulated garbage)	
			- exceptions: = ships operate exclusively within navigable waters of US;	
			= ships operate exclusively between ports/terminals in the continental US;	
			 ships operate exclusively between continental US ports/terminals and Canadian ports/terminals. 	
			 receive medical waste or hazardous waste, or provide list of alternative transporters. 	
			- does not interfere with terminal operations.	
			- conveniently located.	
			- garbage cannot enter water.	
			- holds all required local, state and Federal permits.	
			- ship repair yard exception.	
2.	г	1	Capacity and Exceptions 158.420	
۷.	L	1		
			 receive all garbage ship desires to discharge, except: large quantities of spoiled or damage cargoes not normally 	
			discharged; - from ships not having commercial transactions with that	

SECTION 7.

PASSENGER TERMINAL VULNERABILITY ASSESSMENT (MSM VOL VII, Chapter 2)

Α.	<u>C</u>	ΙΑΙ	RACTERISTICS AND SENSITIVIT	<u>'Y</u>	Remarks
1.	[]	Current Threat Analysis		
			- available:	(3)	
			- unavailable:	(0)	
2.	[]	Port Accessibility		
			- uncontrolled access:	(2)	
			- limited access controls:	(1)	
			- controlled access:	(0)	
3.	[]	Passenger Terminal Volume		
			- over 100,000 per year:	(2)	
			- 10,000 - 100,000 per year:	(1)	
			- under 10,000	(0)	
4.	ſ	1	DoD Assets	(3)	
٠.		,			
			- yes:	(1)	
			- no:	(0)	
				(total)	
В.	<u>P</u>	OF	RT SECURITY FORCE CHARACT	<u>ERISTICS</u>	
1.	[]	Description of Force		
			- no security guard force:	(12)	
			- security manager, no guard force:	(9)	
			- security manager/guard force, but little or no training:	(6)	
			- security manager, trained personnel but, not fully equipped:	(3)	
			- security manager, trained & fully equipped personnel	(1)	

			 security manager, trained & fully 		Remarks
			equipped personnel; regular		
			training exercises conducted:	(0)	
_				(total)	
C.	<u>PI</u>	HY.	SICAL SECURITY CHARACTER	RISTICS	
1.	[]	Landside		
			- no physical security measures:	(4)	
			 perimeter fencing, landside lighting only: 	(3)	
			 fencing/lighting and live patrols or surveillance systems: 	(2)	
			fencing/lighting and electronic surveillance systems:	(1)	
			- fencing/lighting and live & elect. surveillance systems:	(0)	
2.	[]	Waterside		
			- no waterside security measures:	(6)	
			- lighting only:	(5)	
			- live surveillance only:	(4)	
			- single electronic surveillance system.:	(3)	
			- multiple electronic surveillance systems:	(2)	
			 electronic & live surveillance systems/patrols 	(1)	
			- electronic & live surveillance systems/patrols and lighting:	(0)	
				(total)	
D.			SICAL CHARACTERISTICS OF	PASSENGER	
	<u>TE</u>	<u>ER</u>	<u>MINAL</u>		
1.	[]	Terrain		
			- built up, commercial:	(2)	
			- mountainous, forested, undeveloped:	(1)	
			- open/clear area, undeveloped	(0)	

2.	[]	Routes of Access and Egress		Remarks
			- expressways:	(3)	
			- major highways:	(2)	
			- city streets:	(1)	
			- less frequently travelled roads	(0)	
3.	[]	Rail Accessibility		
			- gates open continuously:	(3)	
			- gates open only when in use:	(2)	
			- unused rail access:	(1)	
			- no rail access:	(0)	
4.	[]	Water Channels		
			- more than 3 choke points:	(3)	
			- 1 - 3 choke points:	(2)	
			- no choke points:	(1)	
			·	(total)	
E.	С	O۱	MMUNICATIONS	, ,	
1.	ſ		None:	(4)	
2.		_	Local Only		
	٠	•	- non-secure:	(3)	
			- secure:	(2)	
3.	ſ	1	Local, State, and Federal	(=/	
•	٠	•	- non-secure:	(1)	
			- secure:	(0)	
			- Scourc.	(total)	
_	6	ΠC	TAINABILITY	(total)	
1.	L]	G	400	
			- 1 day:	(8)	
			- 3 days:	(6)	
			- 7 days:	(4)	
			- indefinite:	(2)	

	2.	[] Medium Threat - attack	likely	Remarks
		- 1 day:	(7)	
		- 3 days:	(5)	
		- 7 days:	(3)	
		- indefinite:	(1)	
3.	r 1	Low Threat - terrorist activity pos		
		- 1 day:	(6)	
		- 3 days:	(4)	
		- 7 days:	(2)	
		- indefinite:	(0)	
		indoninio.	(total)	
G	RF:	SPONSE TIME - SECURITY PERSO		
). 1.		Police Patrol		
••		- 30 minutes or less:	(2)	
		- 30 - 60 minutes:	(3)	
2		- 60 minutes or more:	(4)	
۷.	[]	•		
		- 30 minutes or less:	(1)	
		- 30 - 60 minutes:	(2)	
		- 60 minutes or more:	(3)	
3.	[]	SWAT		
		- 30 minutes or less:	(0)	
		- 30-60 minutes:	(1)	
		- 60 minutes or more:	(2)	
			(total)	
Н.	RE	SPONSE TIME - EMERGENCY PER	SONNEL	
1.	[]	Fire Department		
		- 15 minutes or less:	(1)	
		- 15 - 45 minutes:	(2)	
		- 45 minutes or more:	(3)	

2.	[]	Pollution Response Team		Remarks
			- 15 minutes or less:	(0)	
			- 15 - 45 minutes:	(1)	
			- 45 minutes or more:	(2)	
				(total)	
I.	<u>P</u>	RC	OXIMITY TO URBAN AREAS		
1.	[]	Description		
			- over 100,000 people:	(7)	
			- 50,000 - 100,000 people:	(6)	
			- less than 50,000 people and		
			- city of 100,000 less than		
			20 miles away:	(5)	
			 city of 100,000 is 20 - 50 miles away: 	(4)	
			- city of 100,000 is 50 - 100 miles away:	(3)	
			- city of 100,000 more than 100 miles away:	(2)	
			- isolated/rural countryside	(1)	
				(total)	
J.	G	EC	OGRAPHIC LOCATION		
1.	[]	Description		
	-	-	- OCONUS (under CG jurisdiction):	(8)	
			- East or West Coast:	(6)	
			- Gulf Coast:	(4)	
			- Alaska, Hawaii, Northwest,	(`,	
			Central, or New England:	(2)	
				(total)	

K.	<u>P</u>	RC	<u>XIMITY TO INTERNATIONAL BOR</u>	<u>DERS</u>	Remarks
1.	[]	High Threat		
			- 0 - 100 miles:	(3)	
			- 101 - 500 miles:	(2)	
			- over 500 miles:	(1)	
			- islands:	(0)	
2.	[]	Medium Threat		
			- 0 - 100 miles:	(1)	
			- 101 - 500 miles:	(1)	
			- over 500 miles:	(0)	
			- islands:	(0)	
3.	[]	Low Threat		
			- 0 - 100 miles:	(1)	
			- 101 - 500 miles:	(0)	
			- over 500 miles:	(0)	
			- islands:	(0)	
				(total)	

L.	SU	JN	MARY A	SSESSMEI	<u>NT</u>		Remarks
1.	[]	Total Sco	ores:			
			Sect:	Score:	Sect:	Score:	
			Α		F		
			В		G		
			С		Н		
			D		I		
			E		J		
					K		
				TOTAL POIN			
2	r	1	Range of	f Vulnerabi			
۷.		J					
			- [] Very	/Low (0-10	points)		
			- [] Low	(11 - 25 poir	nts)		
			- [] Med	ium (26 - 50	points)		
			- [] High	n (51- 70 poir	nte)		
			- [] Very	/ High (71-85	points)		

SECTION 8.

PHYSICAL INFORMATION

PURPOSE

Physical information is collected to: (1) have information readily available to assist in making a proper and well informed response to an emergency; (2) document annual equipment tests and structural surveys of piers, moorings, and other critical structures on the waterfront facility; and (3) gather other physical information required for contingency planning and port security. Disclosure of some of this information by facility operators may be voluntary and subject in part to the Privacy Act of 1974 (5 U.S.C. 552a). However, facility operators should be made aware that the lack of such information may impair the Coast Guard's response in the event of an emergency.

Name/Position		Phone Nos.
Name/Fosition		Filone Nos.
		
		o use MSIS Facility File screens to complete some parts of the followi er information should be recorded in the booklet.)
Ownership:		Use:
•	(e.g. commercial, etc.)	(e.g. petroleum prods, etc.)
LOCATION:	(e.g. commercial, etc.)	(e.g. petroleum prods, etc.)
LOCATION:	(e.g. commercial, etc.)	(e.g. petroleum prods, etc.)
LOCATION:	(e.g. commercial, etc.)	(e.g. petroleum prods, etc.)
LOCATION: Physical Locati	(e.g. commercial, etc.)	(e.g. petroleum prods, etc.)
LOCATION: Physical Locati Latitude: N	(e.g. commercial, etc.) ion:(harbo	(e.g. petroleum prods, etc.)
LOCATION: Physical Locati Latitude: N Name of River:	(e.g. commercial, etc.) fon: (harbo	(e.g. petroleum prods, etc.) r, port, etc) W
LOCATION: Physical Locati Latitude: N Name of River:	(e.g. commercial, etc.) fon: (harbo	(e.g. petroleum prods, etc.) 7, port, etc) W River Mile:

D. <u>INVOLVED PARTIES</u>:

Name:	П	ame:	
maille:	"	aille.	
Address:	A	ddress:	
Phone No.	P	hone No.	
Contact:	С	ontact:	
IPN:	IF	'N:	
Distance from nearest pl	ant operation:		
Distance from nearest pl	ant operation:	MAX NO. ALL	
Distance from nearest pl	ant operation: : MAX NO. WORKED	MAX NO. ALL BERTHS	
Distance from nearest pl Distance from tank farm Berthing capacity:	ant operation: : MAX NO. WORKED SIMULTANEOUSLY	MAX NO. ALL BERTHS	
Distance from nearest ploistance from tank farm Berthing capacity: Barges Ships	ant operation: : MAX NO. WORKED SIMULTANEOUSLY	MAX NO. ALL BERTHS	
Distance from nearest ploistance from tank farm Berthing capacity: Barges Ships Size of largest vessel se	ant operation: : MAX NO. WORKED SIMULTANEOUSLY	MAX NO. ALL BERTHS beam	
Distance from nearest ploistance from tank farm Berthing capacity: Barges Ships Size of largest vessel se	MAX NO. WORKED SIMULTANEOUSLY rviced: length	MAX NO. ALL BERTHS beam	

Safety/FF Berths		Piping/SPCC boundaries Facility o			y overviews		
		_ Water intakes		Sensitive areas			
Spill traject	ory	_ NPDES discharg	e points				
Tank farms		_ Hazardous subst	ardous substance release trajectory				
INTERMODAL	INTERFACES: (circl	e)					
RAIL	TRUCKS	CONTAIN	NERS	AIR			
CARGO INFOR	RMATION:						
Cargo	Load/Off	Storage Capacity	No. of Tanks	Typical Vol in Storage	No. Xfers per Month	Xfer	
EQUIPMENT/S	TRUCTURAL TEST	S AND SURVEY	<u>′S</u> :				
Hose Test Info	•						
MATERIAL HANDLED	HOSE NUMBER	LENGTH	DIAMETER	MAWP	DATE TESTED	TES ⁻ PRE	

 	 	

MATERIAL HANDLED	HOSE NUMBER	LENGTH	DIAMETER	MAWP	DATE TESTED	
HANDLED	NUMBER				IESIED	
Pipe Test Info						
MATERIAL HANDLED	DIAMETER	COLOR (IF CODED)	MAWP	DATE TESTED	TEST PRESS	
		(11 22227				
						
Relief Valves:						
TYPE	PIPING	PRESSURE	DATE	OPENING		
	SYSTEM	SETTING	TESTED	PRESSURE		
Pressure Gauges:						
PIPING	DATE	TEST		GAUGE		
SYSTEM	TESTED	PRES	SSURE	PRESSURE		

DEVICE	PIPING SYSTEM	DATE TESTED	
	ity (pier, moorings, piping, crad CONSTRUCTION (steel, concrete, wood, etc.)	DATE OF LAST	CERTIFYING FNTITY
			CERTIFYING ENTITY
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
	CONSTRUCTION	DATE OF LAST	
STRUCTURE	CONSTRUCTION	DATE OF LAST	
STRUCTURE	CONSTRUCTION (steel, concrete, wood, etc.)	DATE OF LAST PHYSICAL SURVEY	
STRUCTURE	CONSTRUCTION (steel, concrete, wood, etc.)	DATE OF LAST PHYSICAL SURVEY	

J. MAJOR POLLUTION RESPONSE EQUIPMENT

1. Containment Boom

SPILL	SERVICE (harbor,		IRT	TOTAL	DATE CG	SAT OR
SIZE UNS/	open water, etc.) AT	DIAMETER	DEPTH	LENG	IH I	EXAMINED
AMP						
MMP						
IVIIVIE			 -			
Boom A	Accessories: Ancho	rs, Rigging, Connec	ione			
Dooili A	decessories. Anono	rs, ragging, comico	.10113			
SPILL	BOOM	ACCESSORY		DATE CG	SAT OR	
SIZE	TYPE	TYPE		EXAMINED		JNSAT
AMP			_			
			_			
			_			
			_		_	
MMP		_	_			
			_		_	
			_			
			_		_ :	
01.			_			
Skimme			_			
	ers	_	CAPACI	тү		SAT OR
Skimme SPILL SIZE		POWER SYSTEM	CAPACI	тү	DATE CG EXAMINE	
SPILL SIZE	ers Skimmer	POWER	CAPACI	тү		
SPILL	ers Skimmer	POWER	CAPACI	тү		
SPILL SIZE	ers Skimmer	POWER	CAPACI	TY		
SPILL SIZE	ers Skimmer	POWER	CAPACI	TY		
SPILL SIZE	ers Skimmer	POWER	CAPACI	TY		
SPILL SIZE	ers Skimmer	POWER		тү		
SPILL SIZE	ers Skimmer	POWER	CAPACI	TY		
SPILL SIZE	ers Skimmer	POWER	CAPACI	TY		

MMP _		 	
	— —		
_		 	

3.	To	w Cap	able Boats					
	SPII SIZI	LL E	BOAT TYPE	LENGTH	ENGINE HP	DATE CG EXAMINED	SAT OR	UNSAT
	AMI	P						
	MM	P						
4.	Со	ntract	ed Clean-up Compar	nies				
	Α.	Name:						
		Addres	ss:					
		Phone						
		FIIONE	• 					
	В.	Name:						
		Addres	ss:					
		Phone	:					
	C.	Name:						
		Addres	ss:					
		DI						
		Phone						

5. Spill Drill Information:

TYPE:				
DATE:				
COMMENTS:				

K. FIRE FIGHTING INFORMATION

1. Fire Department

	Pho	Phone No.:			Distance fr	rom facility:	(kilometers)	
	Do	es the fire department h	nave a fac	ility plan on file?	[] yes	[] no		
2.	Fa	cility/Local Fire De	partme	nt Major Fire Fi	ghting Equ	ipment		
	A.	Fire Trucks						
		OWNER		# OF PUMP ENGINES	н.р.	CAPACITY	# OF FIRE MONITORS	RANGE OF MONITOR
	В.	Fire Boats						
		OWNER		# OF PUMP ENGINES	н.р.	CAPACITY	# OF FIRE MONITORS	RANGE OF MONITOR
	C.	Fire Fighting Foam?	[]	/es [] no	т	 Type Foam:	Volume	:
3.	Fa	cility Fire Fighting	Equipm	ent				
	A.	Fire main? [] y	/es [] no				
	В.	# of fire hydrants:						
		Total:	Within bulk liq	100m or 100 yds of uid manifold:				
	C.	Hose information:						
			REQUII NUMBE			OTAL ENGTH		
		1.5 inch hose						
		2.5 inch hose						

4. Facility Fire Extinguishers (i.e. near transfer docks)

A. Types of fire extinguishers (for reference)

	CLASS (size)	SODA ACID (gallons)	FOAM (gallons)	CO2 (lbs)	DC (lbs)
PORTABLE	A-II	2 1/2	2 1/2		
	B-I		1 1/4	4	2
	B-II		2 1/2	15	10
SEMI-PORTABLE	B-III		12	35	20
	B-IV		20	50	30
	B-V		40	100	50
	C-I			4	2
	C-II			15	10

B. List of portable and semi-portable extinguishers

REQ	UIRED	ON F	IAND
NUMBER	CLASS	NUMBER	CLASS

L. PHYSICAL SECURITY EQUIPMENT

	A.	Date of last security	survey:	
--	----	-----------------------	---------	--

B. New Survey Needed? [] yes [] no

C. If yes, details:

ELEMENT	YES OR NO	ТҮРЕ	REMARKS
Access control system			
Security ID cards			-
Perimeter Security (fence, etc.)			
Lighting (type, number)			
Intrusions detection (alarms)			
Security force			
Emergency Plans			
Communications			

SECTION 9.

FACILITY TARGETING/RISK ASSESSMENT

[To be developed]

SECTION 10.

SIGNATURES AND REVIEWERS REMARKS

This inspection bookiet is comprised of the follow	ring sections: (check the appropriate boxes)			
[] Section 1 (Designated Waterfront Facility)	 Section 6 (MARPOL Reception Facility) Section 7 (Passenger Terminal Vulnerability Assessment) Section 8 (Physical Information) Section 9 (Facility Targeting/Risk Assessment) Section 10 (Signatures and Reviewers Remarks) 			
[] Section 2 (LNG Facility)				
[] Section 3 (LHG Facility)				
[] Section 4 (Bulk Liquid Facility)				
[] Section 5 (Mobile Bulk Liquid Facility)				
The inspection documented in this booklet was co	ompleted by the U. S. Coast Guard on			
O'markana at OO Tarana kan kan	(date)			
Signature of CG Team Leader:	Date:			
Signature of Facility Representative:	Date:			
REVIEWERS REMARKS:				
_				
_				
-				
_				
_				
_				
_				

_			
_			